



## **Protect Cargo and Deliver More Per Day**

Spend less time loading and unloading with the Wabash Curtainside Body. With the cargo-loading ability of a platform truck, plus the protection of an enclosed van, that's an accessible, quick-loading solution to get cargo there safely and on-schedule.

#### **FEATURES**

- Durable, PVC-coated polyester curtains with white acrylic lacquer finish, horizontal and vertical webbing on 2" centers, and stainless-steel buckles and ball-bearing rollers
- Heavy-duty, flat FiberPanel® (FRP) front bulkhead and steel front frame
- Three-position, knee-action rolling side posts that snap open, roll out of the way and snap back into place
- Premium roll-up rear door with 6" header
- Solutions available for traditional, alternative fuel and electrified chassis

# **Specifications**

### **Single**

WIDTH	LENGTH			HEIGHT		
		85"	91"	97"	103"	109"
96" or 102"	18′	•	•	•	•	•
	20'	•	•	•	•	•
	22'	•	•	•	•	•
	24'	•	•	•	•	•
	26'	•	•	•	•	•
	28′	•	•	•	•	•

Available sizes limited by chassis type

### **Double**

WIDTH	LENGTH	HEIGHT			
		97"	103"	109"	
96" or 102"	22'	•	•	•	
	24'	•	•	•	
	26′	•	•	•	
	28'	•	•	•	

• Available sizes limited by chassis type

Chassis Type	• Cab			
Side Wall - Curtainside	28 oz. 2x2 PVC-coated polyester curtains with white acrylic lacquer finish     Horizontal and vertical webbing     Stainless-steel buckles and ball-bearing rollers     Three-position rolling side posts     Two quick closures     Extruded-aluminum cantilever rail			
Side Wall - Non Curtainside	FRP white panels			
Front	FRP white front wall     Square front with no wind deflector			
Rear Frame	<ul> <li>Painted galvannealed steel</li> <li>14 ga. header</li> <li>12 ga. corner posts</li> <li>10 ga. one-piece V-groove threshold</li> <li>Internal gussets</li> </ul>			
Rear Door	Premium roll-up with 6" header     Maximum Security (MS) lock			
Floor	1-1/8" laminated hardwood			
Subframe	<ul> <li>3" I-beam cross members on 12" C/L</li> <li>4" I-beam longsills</li> <li>5" structural channel perimeter (curtainside)</li> <li>Full-perimeter steel reinforcing aluminum rub rail (FRP wall only)</li> <li>Pre-coated understructure</li> </ul>			
Roof	One-piece .032" aluminum skin     Galvanized-steel anti-snag roof bows on 24" C/L			
Interior Lights	LED dome light with rear switch – hot wired			
Exterior Lights	LED clearance lights     Existing chassis taillights			
Bumper	Pooched ICC			
Additional Features	Two rear grab handles			
Warranty	<ul> <li>1-year white surface and leaks</li> <li>3-year/36,000-mile limited bulkhead-to-bumper warranty</li> <li>5-year limited structural warranty (roof, wall and floor structure)</li> <li>See our warranty policy for details</li> </ul>			

Chassis Type	• Cab
Side Walls	<ul> <li>28 oz. 2x2 PVC-coated polyester curtains with white acrylic lacquer finish</li> <li>Horizontal and vertical webbing</li> <li>Stainless-steel buckles and ball-bearing rollers</li> <li>One three-position rolling side post on each side of body</li> <li>One quick closure on each side of body</li> <li>Extruded-aluminum cantilever rail, each side</li> </ul>
Front	<ul> <li>FRP white front wall</li> <li>Square front with no wind deflector</li> <li>Steel tube front frame, primed and painted white</li> </ul>
Rear Frame	<ul> <li>1/4" steel tube rear corner post and header</li> <li>3/16" steel one-piece V-groove threshold</li> <li>Threshold reinforcement</li> </ul>
Rear Door	Premium roll-up with 6" header     Maximum Security (MS) lock
Floor	1-5/16" board apitong
Subframe	<ul> <li>4" I-beam cross members on 12" C/L</li> <li>4" structural channel longsills</li> <li>6" channel perimeter understructure</li> <li>Precoated understructure</li> </ul>
Roof	One-piece .032" aluminum skin     Galvanized-steel anti-snag roof bows on 24" C/L
Interior Lights	LED dome light with rear switch – hot wired
Exterior Lights	LED clearance lights     Existing chassis taillights
Bumper	Pooched ICC
Additional Features	Two rear grab handles
Warranty	<ul> <li>1-year white surface and leaks</li> <li>3-year/36,000-mile limited bulkhead-to-bumper warranty</li> <li>5-year limited structural warranty (roof, wall and floor structure)</li> <li>See our warranty policy for details</li> </ul>