





Durable Resilience for the Demanding Haul

From appliance delivery, to municipalities, to rental fleets, the Wabash Dry Freight Body is the choice for efficient dry freight delivery. Available in a variety of sizes and packed with features to haul more, protect cargo and resist damage, the Wabash Dry Freight Body is up to any dry freight delivery challenge.

Features

- DuraPlate sidewalls for extreme durability and damage resistance with minimal weight
- One-piece molded V-groove threshold protects rear entry and eases cleaning
- Durable, top internal steel gussets for rear frame reinforcement
- Many options to address bulk items and cargo control challenges
- Solutions available for traditional, alternative fuel and electrified chassis




Specifications

WIDTH	LENGTH	HEIGHT					
		79"	85"	91"	97"	103"	109"
90"	12'	•	•	•			
	14'	•	•	•			
	16'	•	•	•	•		
96"	12'	•	•	•			
	14'	•	•	•			
	16'	•	•	•	•		
	18'		•	•	•		
	20'		•	•	•	•	
	22'		•	•	•	•	•
	24'		•	•	•	•	•
102"	18'		•	•	•		
	20'		•	•	•	•	
	22'		•	•	•	•	•
	24'		•	•	•	•	•
	26'			•	•	•	•
	28'				•	•	•
	30'				•	•	•

• Available sizes limited by chassis type



Translucent roof



Slider ramp



Liftgate

Chassis Type	• Cab
Truck Body Type	• Dry freight
Sidewalls	• .040" smooth aluminum pre-painted white panels
Lining	• Galvanized-steel Z-wall posts; 3/8" plywood sides interior lining (Aluminum only)
Front	• FiberPanel (FRP) white front wall • Molded-composite corners with radius .063" aluminum mill finish wind deflector • Extruded-aluminum radius vertical front corners
Rear Frame	• Painted galvanized steel • 14 ga. header • 12 ga. corner posts • 10 ga. one-piece V-groove threshold • Internal gussets
Rear Door	• Premium roll-up with 6" header • Maximum Security (MS) lock
Floor	• 2" x 6" pine (up to and including 16') • 1-1/8" laminated hardwood (over 16')
Subframe	• 3" formed "C"-channel cross members on 16" C/L (up to and including 16') • 3" I-beam cross members on 12" C/L (over 16') • 4" I-beam longills • Pre-coated understructure

Roof	• One-piece .032" aluminum skin • Galvanized-steel anti-sag roof bows on 24" C/L
Interior Lights	• LED dome light with rear switch - hot wired
Exterior Lights	• LED clearance lights • Existing chassis taillights
Bumper	• Pooched ICC
Warranty	• 1-year white surface and leaks • 3-year/36,000-mile limited bulkhead-to-bumper warranty • 5-year limited structural warranty (roof, wall and floor structure) • See our warranty policy for details

Options

Sidewalls	• 6mm DuraPlate white panels • FRP white panels
Rear Door	• Full opening swing doors
Liftgates	• Contact your representative for more information